

Blue Seal Electric Combi Steamer COMPACT SAPIENS RELOADED EC623RSDW 6 x 2/3 GN



- Compact 510mm wide
- Manual controls
- Electric direct steam version
- LED HVS (High Visibility System) alphanumeric display for temperature, Autoclimate, time and core temperature
- 2.4" LCD-TFT colour display with rapid selection scroller knob for program and setting selection
- Two speed fan
- Over 95 preset recipe programs
- 99 free programs with up to 9 cycles in automatic sequence
- Electronic thermostat 30° – 300°C
- Manual pre-heating
- Auto-reversing fan rotation
- Autoclimate with automatic vent
- Fast-Dry, quick dehumidification of the cooking chamber
- Multipoint core temperature probe
- Automatic LCS (Liquid Clean System) with built-in tank and automatic dispensing
- ECOVAPOR – automatic control of the steam saturation in the cooking chamber
- ECOSPEED – oven optimizes and controls the delivery of energy to maintain correct cooking temperature
- Externally connected hand shower
- USB connection

GENERAL FEATURES

- Direct Steam injection system
- Perfectly smooth, water tight chamber
- Double tempered glass door with air chamber and interior heat-reflecting glass reduces head radiation towards operator
- Hinged inner glass for easy cleaning
- Adjustable door hinge for optimal seal
- Fan motor thermic protection
- Low water alarm
- Component cooling system with overheat display control
- Self-diagnosis and fault display
- Oven light
- IPX4 spray-proof and hose proof

OPTIONAL FEATURES

- Right hinged door
- Configuration for connection to extraction hood



Blue Seal Electric Combi Steamer COMPACT SAPIENS RELOADED EC623RSDW 6 x 2/3 GN

Dimensions

Width	510mm
Depth	625mm
Height	880mm
Weight	59kg

Packed dimensions

Width	570mm
Depth	760mm
Height	1020mm
Weight	68kg

Shelves

2/3 GN	6
Shelf Spacings	60mm

Installation requirements

(for precise installation instructions, please refer to the unit's installation manual).

Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

Supply line voltage

400-415V - 50Hz, 3P+N+E

Special voltage options available on request.

Power connection

Total (kW)	5.25
Convection power (kW)	5
Rated Current (A) (400V)	8

Installation clearances

- rear	50mm
- right	500mm*
- left	50mm

*Clearance required on fixed installations for service accessibility.

If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 500mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

Water connection requirements

- Cold water
- Flow pressure (200-500kPa)
- Soft water connection*
- Shut-off valve with return flow inhibitor and dirt filter
- Water supply x2 R³/₄
- R40 waste water connection

(*Water softener may be required. Please refer to installation manual for water treatment values.)



Australia
www.moffat.com.au

New Zealand
www.moffat.co.nz

Australia
Moffat Pty Limited

Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9413 2400
wasaales@moffat.com.au

New Zealand
Moffat Limited

Rolleston
45 Illinois Drive
Izone Business Hub
Rolleston 7675
Telephone 03-983 6600
Facsimile 03-983 6660
sales@moffat.co.nz

Auckland
Telephone 09-574 3150
sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
Moffat 1569 / 18.05

